

НАСАДКИ ДЛЯ РОТОРНЫХ ДОЖДЕВАТЕЛЕЙ ПИОНЕР IRS-700

ПОКАЗАТЕЛИ ПРОИЗВОДИТЕЛЬНОСТИ

Насадка	Давление, Ат	Поток, л/ч	Время одного цикла (360°), с.	Радиус, м	Насадка	Давление, Ат	Поток, л/ч	Время одного цикла (360°), с.	Радиус, м
1,5	1,5	240	136,86	8,0	6.0	1,5	900	119,17	9,0
	2,0	290	110,89	9,0		2,0	1000	122,09	10,0
	2,5	320	99,93	10,0		2,5	1150	129,69	12,0
	3,0	340	98,24	10,3		3,0	1250	119,88	14,0
2.0	1,5	260	121,12	9,0	8.0	1,5	1000	122,03	9,5
	2,0	300	100,2	9,8		2,0	1200	125,78	11,0
	2,5	360	97,21	10,5		2,5	1300	117,58	13,0
	3,0	390	103,35	11,0		3,0	1450	114,48	14,0
2,5	1,5	330	97,47	9,5	2.0LA	1,5	290	114,48	8,0
	2,0	380	97,65	10,5		2,0	340	102,16	8,5
	2,5	440	99,39	11,0		2,5	390	97,84	9,5
	3,0	500	101,22	11,3		3,0	420	94,81	10,0
3.0	1,5	420	104,52	10,0	2.5LA	1,5	450	112,39	8,5
	2,0	520	108,21	11,2		2,0	500	101,54	9,3
	2,5	580	107,93	12,0		2,5	600	103,3	10,0
	3,0	700	119,57	12,5		3,0	650	108,26	10,5
4.0	1,5	580	108,47	9,5	3.5LA	1,5	650	107,27	8,7
	2,0	700	120,06	10,0		2,0	700	120,41	10,0
	2,5	800	119,72	11,0		2,5	800	118,82	11,0
	3,0	900	117,91	12,0		3,0	900	118,66	11,5
5.0	1,5	700	115,3	10,5	4.5LA	1,5	680	102,2	9,5
	2,0	850	118,8	11,0		2,0	720	112	10,5
	2,5	950	119,87	12,0		2,5	900	115,41	11,0
	3,0	1050	123,21	14,0		3,0	990	117	12,5